

Standard TC Nozzles

Nb	Flow rate L/min. at 100 bar	Equivalent Orifice size (mm)	Equivalent Orifice size (inch)	Angle °	Exitflex reference	Body length
1	0.57	0.33	0.013	110	63-502/30-EX 1100025	short
2	0.75	0.38	0.015	110	63-502/30-EX 1100033	short
3	0.89	0.41	0.016	110	63-502/30-EX 1100039	short
4	1.10	0.46	0.018	110	63-502/30-EX 1100050	short
5	1.50	0.53	0.021	110	63-502/30-EX 1100067	short
6	1.80	0.58	0.023	110	63-502/30-EX 1100080	short
7	2.30	0.66	0.026	110	63-502/30-EX 11001	short
8	3.40	0.79	0.031	110	63-502/30-EX 110015	short
9	4.60	0.91	0.036	110	63-502/30-EX 11002	short
10	6.80	1.10	0.043	110	63-503/30-EX 11003	long
11	9.10	1.30	0.052	110	63-503/30-EX 11004	long
12	11.40	1.40	0.055	110	63-503/30-EX 11005	long
13	13.70	1.60	0.062	110	63-503/30-EX 11006	long
14	16.00	1.70	0.067	110	63-503/30-EX 11007	long
15	18.20	1.80	0.072	110	63-503/30-EX 11008	long
16	21.00	1.90	0.076	110	63-503/30-EX 11009	long
17	27.00	2.30	0.090	110	63-503/30-EX 11012	long
18	1.10	0.46	0.018	130	63-502/30-EX 1300050	short
19	1.50	0.53	0.021	130	63-502/30-EX 1300067	short
20	1.80	0.58	0.023	130	63-502/30-EX 1300080	short
21	3.40	0.79	0.031	130	63-502/30-EX 130015	short
22	4.60	0.91	0.036	130	63-503/30-EX 13002	long
23	6.80	1.10	0.043	130	63-503/30-EX 13003	long
24	9.10	1.30	0.052	130	63-503/30-EX 13004	long
25	11.40	1.40	0.055	130	63-503/30-EX 13005	long
26	13.70	1.60	0.062	130	63-503/30-EX 13006	long
27	18.20	1.80	0.072	130	63-503/30-EX 13008	long
28	27.00	2.30	0.090	130	63-503/30-EX 13012	long
29	32.00	2.40	0.094	130	63-503/30-EX 13014	long
30	13.70	1.60	0.062	40	63-503/30-EX 4006	long
31	6.80	1.10	0.043	50	63-503/30-EX 5003	long
32	13.70	1.60	0.062	50	63-503/30-EX 5006	long
33	0.39	0.28	0.011	65	63-502/30-EX 650017	short
34	0.57	0.33	0.013	65	63-502/30-EX 650025	short
35	0.75	0.38	0.015	65	63-502/30-EX 650033	short
36	0.89	0.41	0.016	65	63-502/30-EX 650039	short
37	1.00	0.43	0.017	65	63-502/30-EX 650044	short
38	1.10	0.46	0.018	65	63-502/30-EX 650050	short
39	1.50	0.53	0.021	65	63-502/30-EX 650067	short
40	1.80	0.58	0.023	65	63-502/30-EX 650080	short
41	2.30	0.66	0.026	65	63-502/30-EX 6501	short
42	3.40	0.79	0.031	65	63-502/30-EX 65015	short
43	4.60	0.91	0.036	65	63-502/30-EX 6502	short
44	6.80	1.10	0.043	65	63-503/30-EX 6503	long
45	9.10	1.30	0.052	65	63-503/30-EX 6504	long
46	11.40	1.40	0.055	65	63-503/30-EX 6505	long
47	13.70	1.60	0.062	65	63-503/30-EX-6506	long
48	16.00	1.70	0.067	65	63-503/30-EX 6507	long
49	18.20	1.80	0.072	65	63-503/30-EX-6508	long
50	21.00	1.90	0.076	65	63-503/30-EX 6509	long
51	23.00	2.00	0.078	65	63-503/30-EX 6510	long
52	27.00	2.30	0.090	65	63-503/30-EX 6512	long
53	0.57	0.33	0.013	80	63-502/30-EX 800025	short
54	0.75	0.38	0.015	80	63-502/30-EX 800033	short

# HIGH-QUALITY AIRLESS TC NOZZLES FOR GLAZING LINES, CERAMIC INDUSTRY

Nb.	Flow rate L/min. at 100 bar	Equivalent Orifice size (mm)	Equivalent Orifice size (inch)	Angle °	Exitflex reference	Body length
55	0.89	0.41	0.016	80	63-502/30-EX 800039	short
56	1.50	0.53	0.021	80	63-502/30-EX 800067	short
57	1.80	0.58	0.023	80	63-502/30-EX 800080	short
58	2.30	0.66	0.026	80	63-502/30-EX 8001	short
59	3.40	0.79	0.031	80	63-502/30-EX 80015	short
60	4.60	0.91	0.036	80	63-502/30-EX 8002	short
61	6.80	1.10	0.043	80	63-503/30-EX 8003	long
62	9.10	1.30	0.052	80	63-503/30-EX 8004	long
63	11.40	1.40	0.055	80	63-503/30-EX 8005	long
64	13.70	1.60	0.062	80	63-503/30-EX 8006	long
65	16.00	1.70	0.067	80	63-503/30-EX 8007	long
66	18.20	1.80	0.072	80	63-503/30-EX 8008	long
67	21.00	1.90	0.076	80	63-503/30-EX 8009	long
68	0.39	0.28	0.011	95	63-502/30-EX 950017	short
69	0.57	0.33	0.013	95	63-502/30-EX 950025	short
70	0.75	0.38	0.015	95	63-502/30-EX 950033	short
71	0.89	0.41	0.016	95	63-502/30-EX 950039	short
72	1.50	0.53	0.021	95	63-502/30-EX 950067	short
73	1.80	0.58	0.023	95	63-502/30-EX 950080	short
74	2.30	0.66	0.026	95	63-502/30-EX 9501	short
75	3.40	0.79	0.031	95	63-502/30-EX 95015	short
76	4.60	0.91	0.036	95	63-502/30-EX 9502	short
77	6.80	1.10	0.043	95	63-503/30-EX 9503	long
78	9.10	1.30	0.052	95	63-503/30-EX 9504	long
79	11.40	1.40	0.055	95	63-503/30-EX 9505	long
80	13.70	1.60	0.062	95	63-503/30-EX 9506	long
81	16.00	1.70	0.067	95	63-503/30-EX 9507	long
82	18.20	1.80	0.072	95	63-503/30-EX 9508	long
83	23.00	2.00	0.079	95	63-503/30-EX 9510	long
84	27.00	2.30	0.090	95	63-503/30-EX 9512	long

Soft Edge (SE) TC Nozzles

Nb.	Flow rate L/min. at 100 bar	Equivalent Orifice size (mm)	Equivalent Orifice size (inch)	Angle °	Exitflex reference	Body length
85	2.30	0.66	0.026	65	63-502/30-EX-SE 6501	short
86	3.40	0.79	0.031	65	63-502/30-EX-SE 65015	short
87	4.60	0.91	0.036	65	63-502/30-EX-SE 6502	short
88	6.80	1.10	0.043	65	63-503/30-EX-SE 6503	long
89	9.10	1.30	0.052	65	63-503/30-EX-SE 6504	long
90	11.40	1.40	0.055	65	63-503/30-EX-SE 6505	long
91	13.70	1.60	0.062	65	63-503/30-EX-SE 6506	long
92	4.60	0.91	0.036	80	63-502/30-EX-SE 8002	short
93	6.80	1.10	0.043	80	63-503/30-EX-SE 8003	long
94	9.10	1.30	0.052	80	63-503/30-EX-SE 8004	long
95	11.40	1.40	0.055	80	63-503/30-EX-SE 8005	long
96	4.60	0.91	0.036	95	63-502/30-EX-SE 9502	short
97	6.80	1.10	0.043	95	63-503/30-EX-SE 9503	long
98	9.10	1.30	0.052	95	63-503/30-EX-SE 9504	long
99	11.40	1.40	0.055	95	63-503/30-EX-SE 9505	long
100	4.60	0.91	0.036	110	63-502/30-EX-SE 11002	short
101	6.80	1.10	0.043	110	63-503/30-EX-SE 11003	long
102	9.10	1.30	0.052	110	63-503/30-EX-SE 11004	long
103	11.40	1.40	0.055	110	63-503/30-EX-SE 11005	long



**Exitflex SA**  
 Chemin de la Crétaux 2  
 1196 Gland  
 Switzerland  
 Email: info@exitflex.com

