

Ecoline

Tip sizes 88-492

Angles in degrees and pattern width in inches at 12"(30 cm) from surface
Flow rates at a water pressure of 100 Bar

inch	mm	10°	20°	30°	40°	50°	60°	70°	80°	90°	L/min
		2/3 in.	4/6 in.	6/8 in.	8/10 in.	10/12 in.	12/14 in.	14/16 in.	16/18 in.	18/20 in.	
0.006	0.15	X	X	X	X						0.14
0.007	0.18	X	X	X	X	X					0.18
0.008	0.20	X	X	X	X	X	X				0.22
0.009	0.23	X	X	X	X	X	X				0.25
0.010	0.25	X	X	X	X	X	X	X	X		0.33
0.011	0.28	X	X	X	X	X	X	X	X		0.37
0.012	0.30	X	X	X	X	X	X	X	X	X	0.47
0.013	0.33		X	X	X	X	X	X	X	X	0.57
0.014	0.35		X	X	X	X	X	X	X	X	0.65
0.015	0.38		X	X	X	X	X	X	X	X	0.72
0.016	0.40		X	X	X	X	X	X	X	X	0.91
0.017	0.43		X	X	X	X	X	X	X	X	0.98
0.018	0.45		X	X	X	X	X	X	X	X	1.10
0.019	0.48		X	X	X	X	X	X	X	X	1.30
0.020	0.50		X	X	X	X	X	X	X	X	1.40
0.021	0.53		X	X	X	X	X	X	X	X	1.52
0.022	0.55		X	X	X	X	X	X	X	X	1.65
0.023	0.58		X	X	X	X	X	X	X	X	1.83
0.024	0.60		X	X	X	X	X	X	X	X	1.95
0.025	0.64			X	X	X	X	X	X	X	2.13
0.026	0.66			X	X	X	X	X	X	X	2.46
0.027	0.69			X	X	X	X	X	X	X	2.50
0.028	0.71			X	X	X	X	X	X	X	2.85
0.029	0.74			X	X	X	X	X	X	X	2.95
0.030	0.76			X	X	X	X	X	X	X	3.28
0.031	0.79			X	X	X	X	X	X	X	3.42
0.032	0.81			X	X	X	X	X	X		3.73
0.033	0.84			X	X	X	X	X			3.80
0.034	0.86			X	X	X	X	X			4.12



BENEFITS OF USING EXITFLEX ECOLINE TIP

- Universal tip to fit most manufacturers guards
- Individually tested for consistent flow rate and spray angle
- Super-hard carbide for longer useful fan pattern life
- Easy cleaning, simply turn the tip and rinse
- Feathered edges, no tails
- Great finish at reduced spraying pressure
- Less overspray, with easiest pattern overlap
- Huge selection of tip sizes, with as many as 207 different sizes,