

# Line Marking

## Tip sizes 88-490

Angles in degrees and pattern width in inches at 12"(30 cm) from surface  
Flow rates at a water pressure of 100 Bar

inch	mm	10° 2/3 in.	20° 4/6 in.	30° 6/8 in.	40° 8/10 in.	50° 10/12 in.	60° 12/14 in.	70° 14/16 in.	80° 16/18 in.	90° 18/20 in.	L/min
0.011	0.28		X	X	X						0.37
0.012	0.30		X	X	X						0.47
0.013	0.33		X	X	X	X					0.57
0.014	0.35		X	X	X	X					0.65
0.015	0.38		X	X	X	X	X				0.72
0.016	0.40		X	X	X	X	X				0.91
0.017	0.43		X	X	X	X	X	X			0.98
0.018	0.45		X	X	X	X	X	X			1.10
0.019	0.48		X	X	X	X	X	X	X		1.30
0.020	0.50		X	X	X	X	X	X	X		1.40
0.021	0.53		X	X	X	X	X	X	X		1.52
0.022	0.55		X	X	X	X	X	X	X	X	1.65
0.023	0.58		X	X	X	X	X	X	X	X	1.83
0.024	0.60		X	X	X	X	X	X	X	X	1.95
0.025	0.63		X	X	X	X	X	X	X	X	2.13
0.027	0.68		X	X	X	X	X	X	X	X	2.50
0.029	0.73		X	X	X	X	X	X	X	X	2.95
0.031	0.78		X	X	X	X	X	X	X	X	3.42
0.033	0.84		X	X	X	X	X	X	X	X	3.80
0.035	0.89		X	X	X	X	X	X	X	X	4.30
0.037	0.94			X	X	X	X	X	X	X	5.10
0.039	0.99			X	X	X	X	X	X	X	5.50
0.041	1.04			X	X	X	X	X	X	X	6.15
0.043	1.09			X	X	X	X	X	X	X	6.80
0.045	1.14			X	X	X	X	X	X		7.40
0.047	1.19			X	X	X	X	X	X		7.94
0.049	1.24			X	X	X	X	X			8.50
0.051	1.03			X	X	X	X	X			9.10
0.053	1.35			X	X	X	X	X			9.80
0.055	1.40			X	X	X	X	X			11.00



### BENEFITS OF USING EXITFLEX LM TIP

- Universal tip to fit Graco (RAC V) and Titan guards
- Individually tested for consistent flow rate and spray angle
- Super-hard carbide for longer useful fan pattern life
- Easy cleaning, simply turn the tip and rinse
- Designed specifically to spray lines in parking lots, on roads, crosswalks, airport runways, etc
- Sharp edges, for perfect lines, with no fuzzy edges or thin spots
- Suitable for heavy and thin paints
- Huge selection of tip sizes, with as many as 189 different sizes, perfectly adapted to thick and thin materials