

Premium Standard



Tip sizes 88-491

Angles in degrees and pattern width in inches at 12"(30 cm) from surface
Flow rates at a water pressure of 100 Bar

inch	mm	10°	20°	30°	40°	50°	60°	70°	80°	90°	L/min
		2/3 in.	4/6 in.	6/8 in.	8/10 in.	10/12 in.	12/14 in.	14/16 in.	16/18 in.	18/20 in.	
0.007	0.18	X	X	X	X	X					0.18
0.008	0.20	X	X	X	X	X					0.22
0.009	0.23	X	X	X	X	X	X				0.25
0.010	0.25	X	X	X	X	X	X	X			0.33
0.011	0.28	X	X	X	X	X	X	X	X	X	0.37
0.012	0.30	X	X	X	X	X	X	X	X	X	0.47
0.013	0.33	X	X	X	X	X	X	X	X	X	0.57
0.014	0.35	X	X	X	X	X	X	X	X	X	0.65
0.015	0.38	X	X	X	X	X	X	X	X	X	0.72
0.016	0.40	X	X	X	X	X	X	X	X	X	0.91
0.017	0.43	X	X	X	X	X	X	X	X	X	0.98
0.018	0.45	X	X	X	X	X	X	X	X	X	1.10
0.019	0.48	X	X	X	X	X	X	X	X	X	1.30
0.020	0.50	X	X	X	X	X	X	X	X	X	1.40
0.021	0.53	X	X	X	X	X	X	X	X	X	1.52
0.022	0.55	X	X	X	X	X	X	X	X	X	1.65
0.023	0.58		X	X	X	X	X	X	X	X	1.83
0.024	0.60		X	X	X	X	X	X	X	X	1.95
0.025	0.63		X	X	X	X	X	X	X	X	2.13
0.027	0.68		X	X	X	X	X	X	X	X	2.50
0.029	0.73		X	X	X	X	X	X	X	X	2.95
0.031	0.78		X	X	X	X	X	X	X	X	3.42
0.033	0.84		X	X	X	X	X	X	X	X	3.80
0.035	0.89		X	X	X	X	X	X	X	X	4.30
0.037	0.94		X	X	X	X	X	X	X	X	5.10
0.039	0.99		X	X	X	X	X	X	X	X	5.50
0.041	1.04		X	X	X	X	X	X	X	X	6.15
0.043	1.09			X	X	X	X	X	X	X	6.80
0.045	1.14			X	X	X	X	X	X	X	7.40
0.047	1.19			X	X	X	X	X	X	X	7.94
0.049	1.24			X	X	X	X	X	X	X	8.50
0.051	1.03			X	X	X	X	X	X	X	9.10
0.053	1.35			X	X	X	X	X	X	X	9.80
0.055	1.40			X	X	X	X	X	X		11.00
0.057	1.45			X	X	X	X	X	X		11.80
0.059	1.50			X	X	X	X	X	X		12.50
0.061	1.55				X	X	X	X	X		13.70



BENEFITS OF USING EXITFLEX PREMIUM STANDARD TIP

- Universal tip to fit most manufacturers guards
- Individually tested for consistent flow rate and spray angle
- Super-hard carbide for longer useful fan pattern life
- Easy cleaning, simply turn the tip and rinse
- Ideal for large jobs, in residential and/or commercial applications
- Huge selection of tip sizes, with as many as 284 different sizes