

TWINTIP

Tip sizes 88-493

Angles in degrees and pattern width in inches at 12"(30 cm) from surface
Flow rates at a water pressure of 100 Bar

inch	mm	20°	40°			50°			60°	L/min
		4/6 in.	8/10 in.	OR		10/12 in.	OR	12/14 in.		
SELECT THE SECOND ANGLE										
0.012	0.30	X	X	OR		X	OR	X		0.47
0.013	0.33	X	X	OR		X	OR	X		0.57
0.014	0.35	X	X	OR		X	OR	X		0.65
0.015	0.38	X	X	OR		X	OR	X		0.72
0.016	0.40	X	X	OR		X	OR	X		0.91
0.017	0.43	X	X	OR		X	OR	X		0.98
0.018	0.45	X	X	OR		X	OR	X		1.10
0.019	0.48	X	X	OR		X	OR	X		1.30
0.020	0.50	X	X	OR		X	OR	X		1.40
0.021	0.53	X	X	OR		X	OR	X		1.52
0.022	0.55	X	X	OR		X	OR	X		1.65

X All tips are delivered with a first angle of 20°

X The second angle can be of 40°

X The second angle can be of 50°

X The second angle can be of 60°



BENEFITS OF USING EXITFLEX TWINTIP

- Universal tip to fit most manufacturers guards
- Individually tested for consistent flow rate and spray angle
- Super-hard carbide for longer useful fan pattern life
- Easy cleaning, simply turn the tip and rinse
- 2 angles in one tip !